



SolirocTM

SOLID AS A ROCK



#LegrandImprovingLives



Ideal for strength and durability in public applications

Think Soliroc for strength and design, the ideal choice for exposed areas at the mercy of vandals.



Safety of your switches & powerpoints is our number one priority. Introducing, Soliroc, our robust IK10 range, combining brute strength with an appealing design aesthetic for guaranteed protection.

Ideal for high-demand applications with heavy pedestrian traffic.

- Detention centres & correctional facilities
- Public park facilities
- Shopping centres
- Childcare centres
- Schools & Universities



High Level Impact Resistance IK10 The promise of strength and durability

All Soliroc products have successfully undergone intensive testing to ensure we can offer you maximum security.



IK 10: MAXIMUM IMPACT RESISTANCE | All Soliroc products can withstand impacts of 20 joules



IK 10: MAXIMUM PULL-OFF RESISTANCE | Rounded plate shape to prevent a firm grasp




IP 55: GUARANTEED WEATHERPROOF | On the main functions required for outdoor installations





SAFE, RELIABLE & EASY TO INSTALL

Installing Soliroc™ requires a wall box, mounting frame, mechanism and coverplate




Legrand flush-mounting box BATIBOX



Dry partitions Concrete Masonry

3 FLUSH-MOUNTING BOX VERSIONS
Accept all Soliroc functions



SOLIROC 1 AND 2 GANG SURFACE BOXES
For surface-mounting installations



UNIVERSAL SUPPORT FRAME
Just snap in any Soliroc mechanism
71 mm fixing centre.
Can be assembled for multi-gang installations



ARTEOR ADAPTOR OPTIONS
- with cover
- with cover and key
- without cover
For fitting Arteor functions



METAL ALLOY
Finishing plate for guaranteed toughness in 1, 2 or 3 gang (horizontal or vertical mounting). Strong resistance against scratches, graffiti and lighter flames. Great resistance to salt - suitable for coastal areas

SMOOTH TRANSITION
Between mechanism and cover plate, preventing a firm grasp on the device

BLANKING PLUGS
To cover the 4 fixing points. Can only be removed by drilling. Replacement plugs available

FLUSH-MOUNTING BOXES

UNIVERSAL SUPPORTS

SOLIROC™

ARTEOR™

Below is a small selection of Arteor™ mechanisms suitable for use with the Soliroc™ range. Over 50+ mechanisms available.



Switch
2 module



RJ sockets
Cat 6, 5E & telephone



Television sockets
75 ohm "F" connector



USB female socket
For connecting USB devices



HDMI socket
For digital HD audio/video connection



Socket outlet 240V
10A and 15A autoswitched socket

The following Arteor adaptors support 2-module Arteor mechanisms.



Adaptor
without cover



Adaptor
with cover



Adaptor
with cover and key

Please visit the Arteor catalogue or www.ecat.legrand.com.au to view all mechanisms.

Soliroc

Complete units



77893



77894













077895

Suitable for public buildings, unsupervised passageways, car parks, communal areas in buildings
High resistance to IK 10 impacts and humidity
4 fixing points by plugging the plate directly on the wall and 4 blanking plates to be force-mounted on the plate (can only be removed by drilling)
Mechanisms supplied with cover plates, to be equipped with support frames and plates.

Pack	Cat.Nos	Complete products 230/240V a.c.
1	77893	1 gang switch 10A IP55 ● Silver
1	77894	Single GPO 10A IP55 ● Silver
1	077895	Double GPO 10A IP55 ● Silver









Suitable for public buildings, unsupervised passageways, car parks, communal areas in buildings
High resistance to IK 10 impacts and humidity
4 fixing points by plugging the plate directly on the wall and 4 blanking plates to be force-mounted on the plate (can only be removed by drilling)
Mechanisms supplied with cover plates, to be equipped with support frames and plates.





Pack	Cat.Nos	Switches 10 AX - 230/240V a.c.
1	77811	 2-way switch
1	77821	 Intermediate switch
1	77812	 Illuminated 2-way switch Supplied with lamp Cat.No 0 676 86
1	77814	 2-way indicatorswitch Supplied with lamp Cat.no 0 676 86
1	77822	 Double pole switch 20 A
1	77841	 Push-buttons 6 A - 230 VA - IK 10 - IP 55 Two-way push-button NO-NC contact
1	77823	 Switches 10 AX - 230/240V a.c. Without neutral, 2-wire - 1000 W For controlling 1000 W incandescent and halogen lighting 230 VA, 400 VA ELV halogen fluo lighting For controlling a motor (eg: Ventilation) - 230/240V a.c. Time delay from 25 s to 15 mins
1	77874	 Keyswitches - IK 10 - IP 54 To be equipped with European key barrel Cat.No 0 697 95 2-position keyswitch 1 contact - 2 poles - 6 A - 230 V Key extracted in central position without changing the status of the contacts (on/off)
1	77875	 3-position key-operated push-button Changeover switch with off position - 6 A - 230 V Key extracted in off position
1	697 95	 European key barrel. Supplied with 1 set of 3 keys.











Suitable for public buildings, unsupervised passageways, car parks, communal areas in buildings
High resistance to IK 10 impacts and humidity

Pack	Cat.Nos	Illuminated sign 230/240V a.c. - IK 10 - IP 55
1	77868	 Mechanism incorporating white LEDs and a pivoting window which can take preprinted labels 2 choices of power rating (0.2 W or 1 W)
1	77867	 Passage lighting - IK 10 - IP 55 For lighting a staircase, etc 230/240V a.cA Supplied complete with: - Soliroc plate 5 modules - 1 set of 4 blanking plates that can be removed by drilling Mechanism: screw fixing in flush-mounting boxes, depth 40 mm Supplied with: - 16 white LEDs (2 W) - 1 x 5 modules Batibox support
1	77851	 Plates - IK 10 1-gang plate 110 x 110 mm
1	77852	 2-gang plate 110 x 181 mm Horizontal or vertical mounting 71 mm fixing centres
1	77853	 3-gang plate 110 x 252 mm Horizontal or vertical mounting 71 mm fixing centres
1	77891	 Network socket - IK 10 - IP 20 Cat.6 RJ 45 socket - FTP



Pack	Cat.Nos	Supports
10	80251	 For mechanism 2 Modules
1	77884A	Accessories Adaptors for Arteor/Mosaic functions Take 2-module Arteor/Mosaic mechanisms (except special surface-mounting type) Adaptor with lockable cover - IP 55 - IK 10
1	77880	 Adaptor with cover - IP 55 - IK 10
1	77881	 Adaptor without cover - IP 20
5	77896	Replacement blanking plugs Can only be removed by drilling Set of 4 Seals for surface correction Made of foam to compensate for unevenness of the wall For 1-gang plate
1	77885	For 2-gang plate
1	77886	For 3-gang plate
1	77887	Blanking plate 2 modules
1	77866	Fixing accessory  Fits on Batibox boxes for masonry and concrete, for fixing directly in the wall The Soliroc plate can be fixed onto this accessory with no need for drilling or using plugs in the wall 1-gang, can be joined to create 2-gang
1	77883	



Pack	Cat.Nos	1-gang boxes
50	Depth 40 80051	 For 1 gang or 2 modules Drilling diameter 67 mm For wiring accessories using screws or claws
30	80052	Multi-gang boxes For wiring equipment using screws Drilling diameter 67 mm Supplied with 1 removable divider for accommodating extended functions For 71 mm fixing centres Compatible with: Arteor, Mosaic, Valena Life/Allure, Niloé, Kaptika
30	80053	 2-gang or 4/5 modules Horizontal or vertical use
30	80054	 3-gang or 6/8 modules Horizontal or vertical use
30 15	080044 080054	 4-gang or 8/10 modules Horizontal or vertical use
1	80067	Holesaw Holesaw for Batibox 1 to 4 gang with extractor pilot drill with carbide tip  Supplied with centring drill Bi-metallic hole cutter Equipped with an extractor spring Ø67mm 1 to 4 gang boxes For use in the following materials: plasterboard, wood, fibreboard, stainless steel reinforced life M3 HSS teeth Pilot drill with carbide tip
1	77890	Surface-mounting boxes Cannot be used for Cat.Nos 0 778 74/75 Supplied with 4 blanking plugs Take ISO 20 protective conductors  1-gang 110 x 110 x 45 mm
1	77892	 2-gang 110 x 181 x 45 mm Horizontal or vertical mounting 71 mm fixing centres



Masonry square box for 3-gang frame. 2 modules. 40mm depth.

WWW.LEGRAND.COM.AU WWW.LEGRAND.CO.NZ

Legrand Australia

Building 4, Nexus Industry Park
43-47 Lyn Pde Prestons NSW 2170
1300 369 777
www.legrand.com.au

Legrand New Zealand

106-124 Target Road Glenfield
Auckland 0627 New Zealand
0800 476 009
www.legrand.co.nz

